

Imperial College London

ARCHITECTURAL STANDARDS PRODUCT DATA SHEET

M12 RESIN FLOOR FINISHES

RESIN FLOOR FINISHES

M12/110

NBS Create:20-55-77/170

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M12.

MANUFACTURER:

ALTRO LTD

Works Road, Letchworth Garden City

Hertfordshire, SG6 1NW

Tel: 01462 707600

E-mail: enquiries@altro.com

Website: <http://www.altro.co.uk>

Supplier Contact: Altro Customer Care Centre enquiries@altro.com



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range:	Altro Screed 4mm slip resistant
Slip Resistance:	PTV \geq 40
Description:	Solvent-free epoxy resin
FeRFA type:	n/a
Application:	Areas of use: medium/heavy duty where there is a risk of slipping, including dining areas, PE changing areas, laboratories, laundries, custodial areas, canteens, retail and entrance areas
Wear Characteristics:	Medium Duty
Nominal Thickness:	4mm
Service Temperature:	0-60C
Chemical Resistance:	Moderate
Guarantee:	10 year product guarantee.
Life Expectancy:	15 years
Cleaning Method:	Scrubber Dryer

TYPICAL NBS SPECIFICATION

M12: 110 RESIN FLOORING

Standard:	Approved Resin Flooring to Imperial College London Architectural Standards
Location:	To architects finishes schedules.
Base:	As per architects details., Typically sand/cement modified screed, concrete, timber or metal
Priming:	Refer to product data sheet for correct primer—dependant on substrate
Manufacturer:	Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW
Range:	Altro Screed
Type:	Solvent-free epoxy resin
Colour:	All colours approved.
Moisture Content:	Substrate moisture content should not exceed 75% R.H. or 5% moisture content by weight.
Joints:	All vertical joints to be transferred through the cove detail and in-filled with Altro Expand vertical.

For full NBS specification contact Altro