Imperial College London

ARCHITECTURAL STANDARDS PRODUCT DATA SHEET

M12 RESIN FLOOR FINISHES

RESIN FLOOR FINISHES

M12/110 NBS Create:20-55-77/170

PREFERED SUPPLIER INFORMATION

NBS REFERENCE M12. MANUFACTURER: **ALTRO LTD** Works Road, Letchworth Garden City Hertfordshire, SG6 1NW Tel: 01462 707600 E-mail: <u>enquiries@altro.com</u> Website: <u>http://www.altro.co.uk</u> Supplier Contact: Altro Customer Care Centre <u>enquiries@altro.com</u>

PRODUCT DESCRIPTION

ICL APPROVED SPECI	FICATION
Range:	Altro Screed 6mm
Description:	Solvent-free epoxy resin
FeRFA type:	6
Application:	Areas of use: for areas where there is a low risk of slipping including warehouses and
	factories
Wear Characteristics:	Medium—heavy Duty
Nominal Thickness:	6mm
Service Temperature:	0 to 60C
Chemical Resistance:	Moderate
Guarantee:	10 year product guarantee.
Life Expectancy:	15 years
Cleaning Method:	Scrubber Dryer
_	•

TYPICAL NBS SI M12: 110 RESIN F	FLOORING
Standard:	Approved Resin Flooring to Imperial College London Architectural Standards
Location:	To architects finishes schedules.
Base:	As per architects details., Typically sand/cement modified screed, concrete, timber or meta
Priming:	Refer to product data sheet for correct primer—dependant on substrate
Manufacturer:	Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW
Range:	Altro Screed
Type:	Solvent-free epoxy resin
Colour:	All colours approved.
Moisture Content:	Substrate moisture content should not exceed 75% R.H. or 5% moisture content by weight.
Joints:	All vertical joints to be transferred through the cove detail and in-filled with Altro Expand vertical.

