

#### PREFERRED SUPPLIER INFORMATION

NBS REFERENCE M50.

MANUFACTURER:

**ALTRO LTD**

Works Road, Letchworth Garden City

Hertfordshire, SG6 1NW

Tel: 01462 707600

E-mail: [enquiries@altro.com](mailto:enquiries@altro.com)

Website: <http://www.altro.co.uk>

Supplier Contact: Altro Customer Care Centre [enquiries@altro.com](mailto:enquiries@altro.com)



#### PRODUCT DESCRIPTION

##### ICL APPROVED SPECIFICATION

**Range:** Altro Wood Safety

**Description:** Decorative, flexible, PVC Safety Flooring containing Aluminium Oxide granules on the surface.

**Application:** Areas of use include public circulation areas, school corridors, classrooms, receptions, student accommodation.

**Other:** Features Altro Easyclean Maxis PUR™ Technology providing superior cleanability, significantly reducing cleaning and maintenance costs. Slip Resistance pendulum measurement of PTV 36 or above low potential for slip & DIN 51130 R10. Suitable for underfloor heating. Can be used with Altro Everlay if a loose lay system is required or Altro Acoustic Underlay 1101 to achieve acoustic properties. Fully compatible with Altro Whiterock wall cladding.

**Environmental:** Achieves a generic BREEAM A+ rating in all Education & Health applications. Contains a bioplasticiser from a renewable resource

**Recyclable:** Post-installation clean off-cuts and all factory waste to be recycled by Altro Ltd via Recofloor. Packaging is 100% recyclable.

**Guarantee:** 10 year product guarantee.

#### TYPICAL NBS SPECIFICATION

**M50: 150A PLASTICS FLOORING**

**Standard:** Approved Safety Flooring to Imperial College London Architectural Standards

**Location:** To architects finishes schedules.

**Base:** Sand cement screed or plywood sub base as architects details.

**Preparation:** Ardex UK Ltd, Arditex smoothing compound or AltroProof epoxy surface damp proof membrane by Altro Ltd

**Manufacturer:** Altro Ltd, Works Road, Letchworth Garden City, Hertfordshire, SG6 1NW

**Range:** Altro Wood Safety

**Type:** Heterogeneous PVC vinyl to BS EN 13845. Classification For Use: BS EN 685/EN ISO 10874 class 34 & 43

**Width:** 2000 mm **Thickness:** 2 mm (EN428/EN ISO 24346) **Format:** Roll

**Dimensions:** 20m x 2 m (40m<sup>2</sup>) (EN426/EN ISO 24341) **Weight:** 2.66kg/m<sup>2</sup> (EN430/EN ISO 23977)

**Colour:** All colours approved.

**Adhesives:** AltroFix 365 for dry area. AltroFix A19 Plus for wet areas.

**Seam welding:** Hot-welding with matching Altro Welding Rod, as clause 680A

**Skirting:** Self-coved skirting with Altro CF38R cove former, C7/C8 top edge or Altro Whiterock overlap

**Accessories:** Clamping drain/channel by Wade International, Visedge VR Edge Strip by Howe Green Ltd.