

PREFERRED SUPPLIER INFORMATION

NBS REFERENCE P21/310

MANUFACTURER: **London Wall Design**

Address **63 Barwell Business Park. Leatherhead Road. Chessington.
KT9 2NY**

Tel 0208 391 8750

E-mail info@londonwall.co.uk

Website: www.londonwall.co.uk

Supplier: Contact:



PRODUCT DESCRIPTION

ICL APPROVED SPECIFICATION

Range: Top hung movable acoustic wall

Product Code Typ100E

Application: Hotels, conference centre, lecture theatres, civic halls, boardrooms/meeting rooms and office environment

Material High density chipboard, steel bracket frame, top and bottom retractable seals, electrically operated worm drive. Custom made panel finishes

Size Up to 10 000mm high and up to 1250 panel width. Panel weight up to 75kg/m²

Other

Pass door panels can be full height single or double. Track type E, Z or K types. Options include curved panels and glass cut-outs. Electric option controls to panel placement seals electronically for perfect sound reduction, ease of use and minimum effort. This system can also be co-ordinated with other control systems such as security and fire alarms and lighting.

Environmental Fully sustainable materials used in production

Recycling Product and components fully re-cyclable & re-useable

Guarantees 12 month labour and part warranty

Production 6 - 8 weeks

TYPICAL NBS SPECIFICATION

Standard NBS L20 540

Range Top hung movable acoustic partition

Manufacturer London Wall Design

Product Reference Type100E

Type Fully electric option moves panels into position and will return them to the closed or stored position all at the press of a wall mounted switch or via remote control

Fire safety Class 1 or class 0 F30 or F60 on request

warranty 12 months labour & parts warranty

Size Up to 10 000mm high x 15000mm wide+ Panel width up to 1250mm each

Material /Finish Replaceable double skin, 3 layer high density chipboard (E1) double skin boards of no less than 19mm each with internal timber/steel twist resistant frame with steel connectors and internal layers of sound reducing materials to achieve the sound insulation rating required

**ARCHITECTURAL STANDARDS
PRODUCT DATA SHEET**

Acoustic Walls

L 20

NBS L20 540

Recycling issues	Product and components fully re-cyclable & re-useable
Enironmental issues	Product free from volatile organic compounds in standard manufacture, timber product supplied with FSC certification
Source	U.K.
Maintenance issues	Servicing recommended by London Wall Design Ltd.
Cleanability	Cleaning instructions detailed in Operation & Maintenance manual.